



1x6 dasso.XTR Bamboo TWO edge grooved decking

Item #: XTR-DK20-G2-PP

PRODUCT DESCRIPTION: Double Grooved Edge 1x6 Bamboo Decking looks luxurious and lasts. 6-foot end matched boards are revolutionizing decking. Have the superior performance of tropical hardwood, but each plank is straight, smooth and color consistent with a truly green story.

SIZE: 3/4+" X 5-3/8+" X 6'

CONSTRUCTION: Strand

JOINERY: End matched, both side lengths grooved

FACE/BOTTOM MILLING: One side reeded face, 3mm ridges

LF PER BUNDLE: 18.00

LF PER PALLET: 1152.00

SF PER BUNDLE: 8.10 sf per bundle

SF COVERAGE PER BUNDLE: 8.27sf per bundle with 3mm spacers

PRE-PRIMED: Yes - WOCA oil

TYPE(S) OF INSTALLATION: Blind clips or Screw (plugs available)

Composition

CONSTRUCTION Strand

PROCESS OR TREATMENT Carbonized and Fused

BINDING PROCESS Fusion Press

FACE/BOTTOM MILLING One side reeded face, 3mm ridges

BINDING AGENT Phenolic resin

BOARD EDGES PROFILE sides rounded 3mm, ends beveled 2mm

JOINERY End matched, both side lengths grooved

Product Information

DECKING GRADE Fused Bamboo

PRODUCT DESCRIPTION Double Grooved Edge 1x6 Bamboo Decking looks luxurious and lasts. 6-foot end matched boards are revolutionizing decking. Have the superior performance of tropical hardwood, but each plank is straight, smooth and color consistent with a truly green story.

CROSS CUT SEALER AVAILABLE Yes

PRE-PRIMED Yes - WOCA oil

FASTENING CLIPS & SCREWS AVAILABLE Yes

PLUGS AVAILABLE Yes

Packaging

PIECES PER BUNDLE 3

SF PER BUNDLE 8.10 sf per bundle

SF COVERAGE PER BUNDLE 8.27sf per bundle with 3mm spacers

LF PER BUNDLE 18 If per bundle

SF PER PALLET 518.4 sf per pallet

BUNDLE PER PALLET 64.00

LF PER PALLET 1152.00

Availability Information

OUT OF WAREHOUSE? Yes

MINIMUM ORDER INCREMENT One bundle

MIXED CONTAINER OR TRUCKLOADS Yes

Dimensions

NUMERIC MM WIDTH FOR CALCULATIONS 137

THICKNESS (DECIMAL) .79 inches

WIDTH (DECIMAL) 5.39 inches

LENGTH (DECIMAL) 72 inches

THICKNESS (MM) 20 mm

WIDTH (MM) 137 mm

LENGTH (MM) 1829 mm

THICKNESS (NOMINAL) 1

WIDTH (NOMINAL) 6

THICKNESS (FRACTION) 3/4+"

WIDTH (FRACTION) 5-3/8+"

LENGTH/LENGTH RANGE 6'

Installation / Warranty

TYPE(S) OF INSTALLATION Blind clips or Screw (plugs available)

CORROSION INFORMATION For applications exposed to salt air, near large bodies of water, swimming pools or other areas where corrosion is more likely to occur, always use Grade 316 stainless steel screws.

WARRANTY RESIDENTIAL 20 Years

WARRANTY COMMERCIAL 20 Years

Technical Information

HARDNESS 3850

JOIST SPAN MAXIMUM 24" (the product can actually span greater than 24", but building codes limit joist span)

FIRE RATING Class A

Eco Properties

FORMAYLDHYDE EMMISSION FROM BINDERS E0 / F****

FSC CERTIFIED AVAILABILITY Yes - as Special Order